

Lock (length, width and draught, respectively, 215, 45 and 17 feet) on the Red River at Selkirk, Man., and the lock at Poupore, Que. A few small locks are operated by provincial authorities.

During 1960, 52,947,000 tons of freight and 29,629 vessels passed through the canals as compared with 51,076,132 tons of freight and 30,559 vessels during 1959. In addition to freight and passenger vessels, thousands of pleasure craft are locked through the canals. Vessels locking at Sault Ste. Marie during 1960 carried 171,932 passengers as compared with 193,721 in 1959.

7.—Lengths of Channels and Dimensions of Locks under the Control of the St. Lawrence Seaway Authority or the Department of Transport

Name	Location	Length of Channel	Locks			
			No.	Minimum Dimensions		
				Length	Width	Depth
		miles		ft.	ft.	ft.
Seaway Canals¹						
Main Route—						
South Shore.....	Montreal to Caughnawaga.....	20	2	766	80	30
Beauharnois.....	Melocheville to Lake St. Francis.....	15	2	766	80	30
Iroquois.....	Iroquois Point.....	1	1	766	80	30
Welland.....	Port Weller, Lake Ontario, to Port Colborne, Lake Erie.....	27.60	8	859	80	30
Non-toll—						
Lachine.....	Montreal to Lachine.....	8.74	5	270	45	14
Cornwall (not through canal).....	Cornwall to Closure dyke.....	3.50	4	270	43.67	14
Sault Ste. Marie.....	St. Mary's Rapids, Sault Ste. Marie.....	1.38	1	900	60	18.25
Department of Transport Canals						
Atlantic Area—						
Canso Canal.....	Canso Causeway, N.S.....	0.70	1	820	80	28
St. Peter's.....	St. Peter's Bay to Bras d'Or Lakes, Cape Breton, N.S.....	0.50	1	300	47.4	17
Richelieu River—						
St. Ours.....	St. Ours, Que.....	0.12	1	339	45	12
Chambly.....	Chambly to St. Johns, Que.....	11.78	9	120.5	23.25	6.5
Ottawa and Rideau Rivers—						
Ste. Anne.....	Junction of St. Lawrence and Ottawa Rivers.....	0.12	1	200	45	9
Carillon.....	Carillon Rapids, Ottawa River.....	0.94	2	200	45	9
Grenville.....	Long Sault Rapids, Ottawa River.....	5.94	5	200	45	9
Rideau.....	Ottawa to Kingston.....	123.53	47	134	33	5.5
	Rideau Lake to Perth (Tay Branch).....	6.82	2	134	33	5.5
Lake Ontario to Georgian Bay—						
Trent.....	Trenton to Peterborough lock, Peterborough.....	88.74	18	175	33	8 ²
	Peterborough lock to Swift Rapids.....	135.71	24	134	33	6
	Swift Rapids to Big Chute.....	8.00	—	—	—	4
	Big Chute to Port Severn.....	8.11	1	100	25	6
	Sturgeon Lake to Lindsay (Scugog Branch).....	10.00	1	142	33	6
	Lindsay to Port Perry (Scugog Branch).....	25.00	—	—	—	4.5
Murray.....	Isthmus of Murray, Bay of Quinte.....	7.53	—	—	—	8.5 ²

¹ Minimum depth of Seaway canals is 27 feet and minimum width 200 feet. Wiley-Dondero canal and two locks near Massena, N. Y., are in United States territory; dimensions are approximately the same as those of Canadian facilities.

² Notice must be given by vessels of more than six-foot draught.

³ With Lake Ontario at elevation of 243 feet.